

EventSeries®

Single Pair Digital Wiring Installation Cable AES-EBU (TPM)



Application

Ideal for fixed wiring of digital equipment and patch boards for professional audio applications. The characteristic impedance of 110 Ohm makes it suitable for digital sound transmissions according to the AES3 standards and also DMX signals.

Cable Design

Conductor	Oxygen Free Tinned Copper (7 x 0,20mm) 0,22m ²
Insulation	Foam Polyethylene (PE)
Pair	2 cores twisted to a pair (Blue / White)
Drain Wire	Stranded tinned copper
Screen	Overall Aluminium/polyester tape (Aluminium Inside) * Screen bonded to Outer Jacket*
Outer Jacket	TPM, Black

Characteristics

- For fixed wiring of digital equipment and patch boards
- 110Ω suitable for digital sound transmission acc. to AES3 and DMX signals
- EasyStrip bonded screen for fast termination

Technical Data


Nom. Capacitance	47	pF/m
Impedance	110	Ω
Conductor Resistance	< 85	Ω/km
Insulation Resistance	> 100	GΩ/km
Attenuation (1 MHz)	2,3	dB/100m
Attenuation (3 MHz)	3,9	dB/100m
Attenuation (10 MHz)	6,9	dB/100m



EventSeries®

Single Pair Digital Wiring Installation Cable AES-EBU (TPM)

Specification

Cross Section	Part Number	Overall Diameter mm	Colour
	110-1601-01	4,20	Black

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.