

Armada™ MFF90 0.6/1kV Marine Grade

Halogen Free • Flame Retardant • Low Temperature



Cable Construction		Technical Characteristics	
Conductor	Stranded flexible plain copper - IEC 60228 class 5	Rated Voltage	0,6/1kV (1,2kV)
Insulation	HF90 LSZH FireFighter™ - IEC 60092-351	Max. Conductor Temperature	+90° C
Colour Code (Add code to below Part Number)	-01 = Black	Min. Recommended Installation Temp.	-15° C
	-02 = Blue	Lowest Operation Temperature	-40° C
	-04 = Red		
	-05 = Grey		
	-13 = Green/Yellow		
	-12 = Brown		
Standards			
IEC60332-1-2, IEC61034, IEC60754, IEC60092-351			
Approved By Germanischer Lloyd, ABS, Det Norske Veritas			

Part Number	MM²	Outer Jacket - Ø (nom.)	Current Rating (A)	Weight (kg/km)
25122	1 x 1.5mm²	3.1	22	21
25124	1 x 2.5mm²	3.6	30	32
25125	1 x 4.0mm²	4.1	39	45
25126	1 x 6.0mm²	4.7	50	63
25128	1 x 10.0mm²	5.7	71	103
25130	1 x 16.0mm²	6.7	94	154
25132	1 x 25.0mm²	8.6	123	244
25134	1 x 35.0mm²	9.7	153	334
25136	1 x 50.0mm²	11.9	196	476
25138	1 x 70.0mm²	13.7	240	671
25165	1 x 95.0mm²	16.2	284	887
25166	1 x 120.0mm²	18.2	331	1125