

SJ00W Portable Cord UL/CSA Listed MSHA Approved 300 V



Cable Construction	
Conductor	Stranded Bare Copper conductors
Insulation	EPDM
Colour Code	2core - Black, White
	3core - Black, White, Green
	4core - Black, White, Red, Green
Outer Jacket	CPE, Black
Temperature Range	-40° C up to +90° C

No. Of Conductors	Conductor Size (AWG)	Conductor Stranding	Current Rating*	Radial Thickness Insulation (mm)	Nom. O.D. (mm)	Total Weight (kg/km)
2	18	16/30	10 A	0.76	7.23	76
3	18	16/30	10 A	0.76	7.75	99
4	18	16/30	7 A	0.76	8.38	115
2	16	26/30	13 A	0.76	7.87	92
3	16	26/30	13 A	0.76	8.38	111
4	16	26/30	10 A	0.76	9.27	145
2	14	41/30	18 A	0.76	8.64	122
3	14	41/30	18 A	0.76	9.27	158
4	14	41/30	15 A	0.76	10.03	198
2	12	65/30	25 A	1.14	10.41	175
3	12	65/30	25 A	1.14	10.92	228
4	12	65/30	20 A	1.14	12.07	271
2	10	104/30	30 A	1.14	13.97	264
3	10	104/30	30 A	1.14	14.48	346
4	10	104/30	25 A	1.14	16.64	462

*(green conductor for earthing only)