


RG213/U 50 Ω

MIL-C-17F 97% Braid (LSZH)



Cable Design

Conductor	Stranded bare copper wire
Stranding	7/0,75 mm
Dielectric	Solid Polyethylene (PE)
Diameter	Ø 7,25 ± 0,18 mm
Braid	Bare copper wire braid
Construction	192x0,18 mm
Coverage	97 %
Outer Jacket	LSZH FireFighter® UV-resistant
Diameter	Ø 10,30 ± 0,18 mm
Colour	Black

Mechanical and Thermal Characteristics

Temperature Range	-30°C up to +70°C
Min. Bending Radius	single 5 x Ø, repeated 10 x Ø
Weight	165,7 kg/km

Electrical Data

Inner Conductor DC	6,0	Ohm/km
Outer Conductor DC	4,4	Ohm/km
Impedance	50±3	Ohm
Capacitance	100	pF/m
Velocity ratio	66	%
Operating Voltage	4,0	kV rms
Test Voltage	9,0	kV rms
Sheath sparking test	5,5	kV
Screening effectiveness 100-900 MHz	>	55 dB



RG213/U 50 Ω

MIL-C-17F 97% Braid (LSZH)

Attenuation

Frequency (MHz)	dB/100m
5	1,2
10	1,8
50	4,3
100	6,4
200	9,5
400	13,7
500	15,3
600	16,9
800	20,4

Frequency (MHz)	dB/100m
1000	23,2
1350	28,4
1500	30,4
1750	33,7
2150	38,9
2250	39,7
2500	42,7
2750	45,7
3000	48,9

Structural Return Loss

Frequency (MHz)	dB
30 - 300	> 31
300 - 600	> 28
600 - 1000	> 27
1000 - 2000	> 24
2000 - 3000	> 22

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact details can be confirmed at point of enquiry