

# EventSeries®

## DMX Data Control Cable 500 V



### Application

The DMX range complies with the requirements of DMX512-A and is an RS-485 based communications protocol that is most commonly used to control stage lighting and effects.

### Cable Design

Conductor	Stranded Tinned Copper (16 x 0,20 mm) 0,5 mm <sup>2</sup>
Insulation	Foam Polyethylene Ø 1,8 ± 0,05 mm
Pair	2 wires twisted to a pair
No. of Pairs	1 Pair : Black, Red 2 Pair : Black, Red, / Yellow, Green
Drain Wire	Stranded Tinned Copper (16 x 0,20 mm)
Shield	Aluminium/polyester tape. (Aluminium inside)
Outer Jacket	LSZH FireFighter®, FRLS or TPE



### Characteristics

- Most commonly used to control stage lighting and effects
- Flame Retardant acc. to IEC 60332-1
- Halogen Free acc. to IEC 60754
- Smoke Density acc. to IEC 61034

### Technical Data

Impedance	110±5	Ω
Tray Rated Voltage	500	V
Test Voltage	2000	V
Service Temperature (static)	-20 °C to +80 °C	
Service Temperature (mobile)	-5 °C to +80 °C	
Weight	34	kg/km

# EventSeries®

## DMX Data Control Cable 500 V

### Specification

Cross Section	Part Number	No. of Pairs	Type	Overall Diameter [mm]	Min. Bending Radius [mm]	Colour
	DMX-01	1	FRLS	5,75 ± 0,3	60	Black
	DMXLSZH-01	1	LSZH FireFighter®	5,75 ± 0,3	60	Black
	DMXLSZH-10	1	LSZH FireFighter®	5,75 ± 0,3	60	White
	DMX-04	1	FRLS	5,75 ± 0,3	60	Red
	DMX-P-01 *	1	TPE	5,75 ± 0,3	60	Black
	DMXLSZH2-01	2	LSZH FireFighter®	8,20 ± 0,5	90	Black

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.