

Armada®

440 Series RS485 Offshore SHF-2 FFxT™



Application

A range of 24awg multi-pair low capacitance cables with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications. These cables utilise FireFighter® FFxT™ performance materials for marine and offshore applications.

Cable Design

Conductor	Stranded tinned copper wire (24awg)
Insulation	Solid PO Ø 1,62 mm
No. of Pairs	1 or 2
Overall Shield	Overall Aluminium/polyester tape
Drain Wire	Stranded tinned copper wire
Overall Braid Shield	Tinned copper wire braid
Outer Jacket	SHF-2 FFxT™ HFFR, UV-Stabilised, Black

Characteristics

- Onshore / Offshore applications
- UV-Stable and colourfast
- Flame retardant acc. to IEC 60332-1
- Halogen Free acc. to IEC 60754-1/2
- Smoke density acc. to IEC 61034-1/2
- IEC60092-359
- Temperature Range -40°C to +90°C



Armada®

440Series RS485 Offshore SHF-2 FFxT™

Specification

Part Number	Formation No. of Pairs	Nom. Outer Jacket Ø mm
M4401P18F4	1 x 2 x 24 awg	6,0 ± 0,2
M4402P18F4	2 x 2 x 24 awg	8,6 ± 0,5

Electrical Characteristics

Nom. Capacitance (cond./cond.) pF/m	Nom. Capacitance (cond./cond./ screen) pF/m	Electrical Resistance Ω/km	Nom. Velocity of Propagation %	Nom. Inductance μH/m	Nom. Impedance Ω
38	75,5	82	66	0,56	110-120

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.