

# FireFighter® 410Series

LSZH 4core 18awg IEC60332-1 600V



## Application

Our 4104C1844 4 core 18awg has a high level of screening to ensure interference free performance on applications requiring high speed data transmission. This cable uses FireFighter® Low Smoke Zero Halogen performance materials.

## Cable Design

Conductor	Stranded tinned copper wire (19/0,25mm) 18awg
Insulation	LSZH FireFighter® Ø 1,80 mm
No. of Cores	4 - Colour coded Black, Red, White, Green
Tape	Polyester overlap
Drain Wire	Stranded tinned copper wire
Overall Shield	Overall Aluminium/Polyester tape
Outer Jacket	LSZH FireFighter® SHF-1

## Characteristics

Colour	Grey RAL 7001
Rated Voltage	600 V
Temperature Range	-20 °C up to +90 °C

## Fire Behaviour

- Flame Retardant acc. to IEC 60332-1
- Halogen Free acc. to IEC 60754
- Smoke Emission acc. to IEC 61034
- Euroclass Eca



# FireFighter® 410Series

LSZH 4core 18awg IEC60332-1 600V

## Specification

Part Number	Formation No. of Cores	Nom. Ø mm ± 10%	Weight kg/km
4104C1844	4 x 18 awg	6,40	75

## Electrical Characteristics

Voltage test core : core V dc x 1 min	Voltage test core : screen V dc x 1 min	Nom. Capacitance pF/m	Nom. Conductor Resistance Ω/km
2000	1000	140,6	21,4

*Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.*