

195 Low Loss Flexible Communication Coax - 50 Ohm

Cable Design

Inner Conductor	Solid plain copper wire	Ø 0,94 mm
Dielectric	Foam Polyethylene (PE)	Ø 2,79 mm
Shield	Aluminium tape	Ø 2,95 mm
Braid	Tinned copper wire braid	Ø 3,53 mm
Outer Jacket	Polyethylene (PE) or LSZH FireFighter®	Ø 4,95 mm



Mechanical and Thermal Characteristics

Bending radius	installed	12,7	mm
	repeated	50,8	mm
Bending moment		0,27	N/m
Weight		30	kg/km
Tensile strength		18,2	kg
Flat plate crush		0,27	kg/mm
Temperature Range	Installation	-40 to +85	°C
	Storage	-70 to +85	°C
	Operating	-40 to +85	°C

Electrical Data

Velocity of propagation		76	%
Dielectric constant		1,56	
Time delay		4,17	ns/m
Impedance		50	Ohm
Capacitance		83,3	pF/m
Inductance		0,21	µH/m
Shielding effectiveness	>	90	dB
DC Resistance	Inner Conductor	24,9	Ohm/km
	Outer Conductor	16,1	Ohm/km
Voltage withstand		1000	V
Jacket spark		3000	V rms
Peak power		2,5	kW



Attenuation & Average Power

Frequency (MHz)	Attenuation (dB/100m)	Avg. Power (kW)
30	6.5	0.89
50	8.4	0.68
150	14.6	0.39
220	17.7	0.32
450	25.5	0.22
900	36.5	0.16
1500	47.7	0.12
1800	52.5	0.11
2000	55.4	0.10
2500	62.4	0.09
5800	98.1	0.06

Specification

Part Number	Type
195502	Polyethylene (PE)
195504	LSZH FireFighter® IEC 60332-1