

BNC1CCT100 - Crimp Plug to suit CT100

75Ω

Full Crimp Plug, Turned Brass Body Nickel Plated with Gold Plated Contact. Suitable for CT100

Connector Design

Crimped Ferrule Hex Crimp size 0.305"

Crimped Contact Pin SQ crimp size 0.068"

Crimp Tool Reference TL-5523 or TL-9565

kit Strain relief boot series 100 - SR1**




| Number | Description | Material | Finish |
|--------|-------------|----------|--------|
| 1 | Body | Brass | Nickel |
| 2 | Insulator | *Delrin | White |
| 3 | Gasket | PVC | Red |
| 4 | C Washer | Steel | Nickel |
| 5 | Spring | SK-5 | Nickel |
| 6 | Washer | Steel | Nickel |
| 7 | Shell | Brass | Nickel |
| 8 | Contact Pin | Brass | Gold |
| 9 | Ferrule | Brass | Nickel |

Unless otherwise specified tolerances are as below

| | |
|------------|--------|
| 0.5-6 | = ±0.2 |
| >6-30 | = ±0.4 |
| >30 -120 | = ±0.6 |
| >120 - 315 | = ±1 |
| 315 - 1000 | = ±1.6 |

ANGLES = ±5°

Recommended Cable Stripping Dimensions (mm)



Delrin is a registered trademark of DuPont™