

RG223/U 50 Ω

DataGuard® Armoured (SWA) MIL-C-17F 98% Braid LSZH FireFighter®

Cable Design

Conductor Stranding	Solid silvered copper 1/0,90 mm
Dielectric Diameter	Solid Polyethylene (PE) Ø 2,95 ± 0,10 mm
Braid 1° Construction Coverage	Silvered copper braid 112x0,30 mm 98 %
Braid 2° Construction Coverage	Silvered copper braid 112x0,30 mm 97 %
Inner Jacket Diameter	LSZH FireFighter®, Black Ø 5,40 ± 0,10 mm
Armour	DataGuard Steel Wire Armour (SWA)
Outer Jacket Diameter	LSZH FireFighter®, Black Ø 9,20 ± 0,50 mm

Electrical Data

Inner Conductor DC	28,0	Ohm/km
Outer Conductor DC	8,0	MOhm*km
Impedance	50±2	Ohm
Capacitance	100	pF/m
Velocity ratio	66	%
Screening effectiveness 100-900 MHz	> 70	dB



RG223/U 50 Ω

DataGuard® Armoured (SWA) MIL-C-17F 98% Braid LSZH FireFighter®

Mechanical and Thermal Characteristics

Temperature Range	-30°C up to +70°C
Weight	250 kg/km
Fire Behaviour	IEC 60332-1-2, IEC 60332-3-24C, IEC 61034-2, IEC 60754-1/2

Attenuation

Frequency (MHz)	dB/100m
50	9,0
100	13,0
200	19,3
400	28,1
500	31,9
600	35,3
860	43,8
1000	48,5

Structural Return Loss

Frequency (MHz)	dB
30 - 300	> 32
300 - 600	> 28
600 - 900	> 23

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact details can be confirmed at point of enquiry