



Armada®

PROFIBUS PA 2x18/7 AWG LSZH-SHF2

<DNV-GL Approved>



Application

Offshore installations, Maritime Environment, RS-485, Indoor/outdoor installation, ISA/SP-50 Fieldbus Type A, Harsh Environments, Profibus PA industrial communication.

Cable Design

Conductor AWG	Stranded Annealed Tinned Copper wire 18/7 AWG (7/0,40mm)
Insulation Diameter	Solid Polyethylene (PE) Ø 3,17 mm nom.
Formation Pair Identification	2 cores twisted to a pair Red / Green
Foil shield	Overall Aluminium/polyester foil, 100% coverage
Braid	Annealed Tinned Copper Wire Braid, 80% nom. coverage
Outer Jacket Colour	XL-HFFR FireFighter® SHF-2 Black, Blue or Orange
Thickness	1,30 mm nom.
Diameter	Ø 9,50 mm
Weight	120 kg/km



Standards

Applicable Standards	DNV-GL certified, IEC 60092-359, IEC 60092-350, IEC 60811-2-1, RoHS-2 2011/65/EU
Flammability Rating	IEC60332-1-, IEC 60332-3-22, IEC 60332-3-24, IEC 60754-1/2, IEC 61034-1/2



Armada®




PROFIBUS PA 2x18/7 AWG LSZH-SHF2

<DNV-GL Approved>

Performance

Impedance	100	Ohm
Max. DC Resistance	22	Ohm/km @ 20 °C
Max. Resistance Unbalance	3	%
Attenuation (@ 39,5 kHz)	0,25	dB/km
Capacitance	48	pF/m
Capacitance Unbalance	1,6	pF/m max.
Velocity of Propagation	68	% nom.
Dielectric Strength	1500	V/minute
Dielectric Strength to Shield	1000	V/minute
Voltage Rating	300	V
Min. Bend Radius	75	mm
Max. Operating Temperature	+90	°C
Min. Operating Temperature	-40	°C
UV resistance	YES	

Specification

Part Number	Type	
AMP118-UAZF2-01	Armada® PROFIBUS DP 2x18/7 AWG LSZH SHF-2 DNV-GL certified - Black	
AMP118-UAZF2-02	Armada® PROFIBUS DP 2x18/7 AWG LSZH SHF-2 DNV-GL certified - Blue	
AMP118-UAZF2-08	Armada® PROFIBUS DP 2x18/7 AWG LSZH SHF-2 DNV-GL certified - Orange	

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.