




# Armada®

Cat.5e 4x2x24/1 AWG F/UTP Horizontal Cable  
DNV GL Certified



## Application

DNV-GL approved Cat5E for Offshore installations, Maritime Environment, High data rates, Indoor use, fixed installations, Ships, High speed & Light craft.

## Cable Design

Conductor AWG	Solid Annealed Bare Copper wire 24/1 AWG
Insulation Diameter	PO Ø 1,07 mm nom.
Formation Pair Identification	2 cores twisted to a pair, 4 pairs total (4x2x24/1 awg) Per TIA/EIA 568-B
Drain Wire	Solid Annealed Tinned Copper
Foil shield	Overall Aluminium/polyester foil, 100% coverage
Outer Jacket Colour Diameter Weight	FR-LSZH SHF-1 or XL-HFFR SHF2 Grey Ø 6.80 mm nom. 55 kg/km



## Standards

Applicable Standards	DNV-GL approved, IEC 60092-359, IEC 60092-350, IEC 61156-5, ISO/IEC 11801, RoHS-2 2011/65/EU
Flammability Rating	IEC 60332-1, IEC 60332-3-22, IEC 60754-1/2, IEC 61034-1/2



# Armada®

Cat.5e 4x2x24/1 AWG F/UTP Horizontal Cable  
DNV GL Certified

## Specification

Part Number	Construction	Shield Type	Outer Jacket
AML5E-FUBS24-ZF1	4x2x24/1 awg	F/UTP	SHF1
AML5E-FUBS24-ZF2	4x2x24/1 awg	F/UTP	SHF2

## Performance

Frequency Range	1 - 100	MHz
Impedance	100	Ohm
Transfer Impedance	Grade 1	
Coupling Attenuation	Type 1	
Max. DC Resistance	94	Ohm/km at 20°C
Max. Resistance Unbalance	2	%
Capacitance Unbalance	1,2	pF/m max.
Propagation Delay Skew	35	ns/100m max.
Dielectric Strength	700	V/minute
Min. Insulation Resistance	5	GOhm • km
Min. Bend Radius	45	mm
Cold Bend		per UL 44, per CSA C22.2 No. 38-95
Max. Operating Temperature	+75	°C
Min. Operating Temperature	-40	°C
UV resistance	YES	



# Armada®

Cat.5e 4x2x24/1 AWG F/UTP Horizontal Cable

DNV GL Certified

## Electrical Properties *Cat. 5e Horizontal Cables \**

Fre- quency (MHz)	Attenuation (dB/100m) 20 °C		PS NEXT Loss (dB)		NEXT Loss (dB)		RL (dB)		PS ELFEXT (dB)		ELFEXT (dB)	
	Typ.	Cat.5e	Typ.	Cat.5e	Typ.	Cat.5e	Typ.	Cat.5e	Typ.	Cat.5e	Typ.	Cat.5e
1	2,0	2,1	68,3	62,3	71,3	65,3	22	20	64	61	67	64
4	3,9	4,1	59,3	53,3	62,3	56,3	25	23	52	49	55	52
10	6,2	6,5	53,3	47,3	56,3	50,3	28	25	44	41	47	44
20	8,8	9,3	48,8	42,8	51,8	45,8	28	25	38	35	41	38
30	10,9	11,5	46,1	40,1	49,1	43,1	27	23,8	35	31,5	38	34,5
60	15,8	16,6	41,6	35,6	44,6	38,6	24	21,1	28	25,4	31	28,4
100	21,0	22,0	38,3	32,3	41,3	35,3	22	18,8	24	21	27	24,0

\* Supplied cables meet minimum Cat. 5e transmission requirements of IEC 61156-5 Ed. 2 and ANSI/EIA/TIA 568-B.2

*Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.*

