



# Modular Audio Visual Connectors

*Entertainment Modular Connectors for Crimp, Screw, Spring, Squich inserts*

## Connector Design

- Enclosures are available in the standard sizes 44.27, 57.27, 77.27 and 104.27.
- Compliant with Crimp, Screw, Spring and Squich connections.
- Dimensions and the fastening are unchanged from the traditional versions for easy upgrades
- Easy thermoplastic replacement levers in case of breakdowns.
- The enclosures provide IP65 degree of protection (in accordance with EN 60529) when locked.
- The range of operating ambient temperature is -40°C ÷ +125 °C.)

LS-TYPE Part No.	
- CHIN	bulkhead mounting housing with lever(s)
- MAPN	surface mounting housing high construction with lever(s)
- MFVN	hood with pegs top entry high construction
- MFON	hood with pegs side entry high construction
- MFVN G	hood with lever(s) and gasket top entry, high construction
- CHCN	covers with pegs
- CHCN G	covers with lever(s) and gasket



### LS-TYPE.

An Ideal solution for the entertainment industry (lighting system power supply and related mixer and dimmer panels), including theatre stages, film sets, radio and TV studios, discos, trade fair booths, concert halls and night public events, both indoors and outdoors, etc.  
All parts are coloured RAL 9005 black to make them suitable for environments where they should not be visible in the dark.



### C-TYPE.

This series has been developed for application in electrical and electronic machinery, control units, electrical panels, control equipment, in industrial environments and in general, wherever a reliable and easily disconnectable connection is required for power and signal circuits



### V-TYPE IP67.

This original design locking lever, due to the verticle closing movement, offers an IP66/IP67/IP69 degree of protection according to EN 60529 when fitted with a complete and coupled connector using ILME standard aluminium hoods with die cast pegs